Abstract 23 Figure 1 Perfusion defect extending beyond the area of scar. A: LGE image shows a subendocardial scar involving the lateral and inferior wall; B: perfusion defect in the lateral and inferior wall; C: high-resolution perfusion map show area of scar (black), areas of ischaemia (dark grey) and normal areas of myocardium (light grey)

24 ASSESSMENT OF THE EFFECTS OF TECHNIQUE ON PULMONARY ARTERIAL PULSE WAVE VELOCITY MEASUREMENT

¹*JR Weir-McCall, ¹A Kamalasanan, ¹DB Cassidy, ¹AD Struthers, ²BJ Lipworth, ¹JG Houston. ¹Division of Cardiovascular and Diabetes Medicine, Medical Research Institute, University of Dundee, Dundee, UK; ²Scottish Centre for Respiratory Research, Medical Research Institute, University of Dundee, Dundee, UK

10.1136/heartjnl-2016-309668.24

Aim The flow-area (QA) technique allows measurement of pulse wave velocity (PWV) from a single phase contrast slice. However

in the pulmonary circulation reflected waves arrive during systole and may cause erroneous measurements using this technique. The aim of the study was to compare three post-processing calculations, one of which avoids the reflected wave, and the other which corrects for it, on the measurement of pulmonary PWV and its reproducibility.

Materials and methods 10 young healthy volunteers (YHV) (30% male, mean age 31.5 ± 7.6) and 20 older healthy volunteers (OHV) (45% male, mean age 60.2 ± 4.0) underwent MRI using phase contrast sequences through the main pulmonary artery (MPA), right pulmonary artery (RPA) and left pulmonary

Abstract 24 Figure 1 Bland-Altman plots comparing interscan PWV repeatability using the 3 techniques in the 3 pulmonary arterial locations

artery (LPA). Measurements were repeated at 6 months in the YHV cohort and on the same visit in the OHV cohort. QA PWV was calculated using three techniques: $QA_{\text{Trad}} = \Delta Q / \Delta A$; $QA_3 = \Delta Q / \Delta A$ (using only the first three datapoints in the reflectionless upstroke); and $QA_{\text{Inv}} = \sqrt{(\sum \Delta A^2 / \sum \Delta Q^2)}$.

Results QA_{Trad} produced significantly higher results than QA_3 ($p < 0.001$) and QA_{Inv} ($p < 0.001$), whilst there was no difference between QA_3 and QA_{Inv} ($p = 0.41$). In scan-rescan reproducibility, QA_{Inv} yielded improved precision over QA_{Trad} and QA_3 : mean (SD) of PWV differences = -0.46 (0.98) ms^{-1} , 0.05 (0.88) ms^{-1} , and 0.01 (0.63) ms^{-1} for the QA_{Trad} , QA_3 , and QA_{Inv} of the MPA

respectively; 0.17 (0.43), 0.19 (0.83) and 0.06 (0.25) ms^{-1} for the QA_{Trad} , QA_3 , and QA_{Inv} of the RPA respectively; and -0.29 (0.31), -0.01 (0.39) and -0.06 (0.32) ms^{-1} for the QA_{Trad} , QA_3 , and QA_{Inv} of the LPA respectively (see Figure 1).

Conclusion Calculations which account for wave reflections yield lower PWV than those that don't suggesting significant confounding effects from these early reflected waves. Combining a phase contrast sequence acquisition through the right pulmonary artery with a post processing technique to account for wave reflections yields the most reproducible measurements of pulmonary PWV.